





















| مدل | مشخصات | | قیمت مصرف کننده (ریال) |
|---------------------|---|--|------------------------|
| IP Telephony | | | |
| GXP1610 |  | 2 line keys with dual-color LED (1 SIP account and up to 2 call appearances) Dual switched 10/100Mbps ports, 132x48 graphical LCD display Without PoE | ۲,۳۰۰,۰۰۰ |
| GXP1615 |  | GXP1615, 1 SIP account, 2 line keys , 3-way conferencing, 3 XML programmable context-sensitive soft keys | ۲,۴۵۰,۰۰۰ |
| GXP1620 |  | The GXP1625 is Grandstream's standard IP phone for small businesses. This Linux-based, 2-line IP Phone includes 3-way conferencing to keep workers in-touch and productive. A 132x48 backlit LCD screen creates a clear display for easy viewing. Without PoE | ۲,۹۲۰,۰۰۰ |
| GXP1625 |  | The GXP1625 is Grandstream's standard IP phone for small businesses. This Linux-based, 2-line IP Phone includes 3-way conferencing to keep workers in-touch and productive. A 132x48 backlit LCD screen creates a clear display for easy viewing.integrated PoE | ۲,۷۵۰,۰۰۰ |
| GXP1628 |  | The GXP1628 is a powerful Gigabit IP phone designed for small businesses. This Linux-based, 2-line IP Phone model includes 8 BLF keys and 3-way conferencing to keep workers in-touch and productive. A 132x48 backlit LCD screen creates a clear display for easy viewing.integrated PoE | ۳,۳۵۰,۰۰۰ |
| GXP1630 |  | The GXP1630 is a powerful Gigabit IP phone designed for small businesses. This Linux-based, 3-line IP Phone model includes 8 BLF keys and 4-way conferencing to keep workers in-touch and productive. A 132x64 backlit LCD screen creates a clear display for easy viewing.integrated PoE | ۵,۰۶۰,۰۰۰ |








| مدل | مشخصات | | قیمت مصرف کننده (ریال) |
|------------|---|---|------------------------|
| GXP1760 |  | GXP1760 SIP telephone, 3 SIP Accounts , 6 x line keys, AC + PoE, 200x80 pixel backlit LCD. | ۵,۲۸۰,۰۰۰ |
| GXP1780 |  | GXP1780 SIP telephone , 4 SIP accounts , 8 dual-color line keys and 4 XML programmable context sensitive soft keys on a 200 x 80 pixel back-lit LCD display screen | ۵,۵۲۰,۰۰۰ |
| GXP1782 |  | GXP1782 SIP telephone , 4 SIP accounts , 8 dual-color line keys and 4 XML programmable context sensitive soft keys on a 200 x 80 pixel back-lit LCD display screen, with dual auto-sensing Gigabit network ports . | ۶,۲۰۰,۰۰۰ |
| GXP2130 v2 |  | 3 dual-color line keys (with 3 SIP accounts) 320x240 TFT color LCD Dual switched auto-sensing, 10/100/1000Mbps Gigabit network ports, PoE | ۴,۷۵۰,۰۰۰ |
| GXP2135 |  | GXP2135 IP phone, 8 lines, 4 SIP accounts , Gigabit speeds and up to 32 virtual BLF/speed-dial keys | ۶,۳۲۰,۰۰۰ |
| GXP2170 |  | GXP2170 12 line keys/line appearances and 6 SIP accounts , includes 48 on-screen digital BLF/speed-dial keys and | ۸,۸۴۰,۰۰۰ |








| مدل | مشخصات | | قیمت مصرف کننده (ریال) |
|------------|---|---|------------------------|
| GXP2140 |  | 4 dual-color line keys (with 4 SIP accounts) 480x272 TFT color LCD Dual switched auto-sensing, 10/100/1000Mbps Gigabit network ports, PoE with Bluetooth, USB | ۵,۵۰۰,۰۰۰ |
| GXP2160 |  | 6 dual-color line keys (with 6 SIP accounts) 480x272 TFT color LCD Dual switched auto-sensing, 10/100/1000Mbps Gigabit network ports, PoE with Bluetooth, USB | ۶,۹۰۰,۰۰۰ |
| GXP2200 |  | 6 lines with up to 6 SIP accounts 480x272 pixel capacitive touch screen TFT LCD Android™ Operating System 2.3 | ۷,۸۸۰,۰۰۰ |
| GXP2200EXT |  | Extension Key Pad for GXP3240 and GXP2140 | ۵,۵۰۰,۰۰۰ |
| GXP2000EXT |  | GXP-2000 Extension Module | ۳,۶۸۰,۰۰۰ |
| GXP2020EXT |  | GXP-EXT 2020 Extension Key Pad | ۴,۳۶۰,۰۰۰ |









| مدل | مشخصات | | قیمت مصرف کننده (ریال) |
|---------------------------|---|---|------------------------|
| IP Video Telephony | | | |
| GXV3240 |  | 4.3 inch (480×272) capacitive (5 points) touch screen TFT LCD 6 lines with up to 6 SIP accounts The phone features integrated Bluetooth, Gigabit ports, a built-in web browser, integrated WiFi | ۱۱,۸۵۰,۰۰۰ |
| GXV3275 |  | 6 lines with up to 6 SIP accounts Dual switched auto-sensing 10/100/1000Mbps network ports, Wi-Fi (802.11b/g/n), PoE+, Bluetooth, USB, SD, HDMI , 7" (1024×600) capacitive (5 points) touch screen TFT LCD Runs the Android™ Operating System 4.2 | ۱۶,۶۰۰,۰۰۰ |
| IP DECT Phone | | | |
| DP750 |  | DP750 Long-range DECT VoIP base station with the capacity to host up to 5 DP720 cordless DECT handsets , set features up to 10 SIP accounts , with up to 10 lines per handset and up to 5 concurrent calls, along with 3-way audio conferencing. | ۴,۲۰۰,۰۰۰ |
| DP720 |  | DP720 DECT cordless handset | ۳,۷۶۰,۰۰۰ |
| مدل | مشخصات | | قیمت مصرف کننده (ریال) |
| IP PBX | | | |
| UCM 6202 |  | UCM6202 IP PBX System, support up to 500 users and 30/45 concurrent calls | ۱۷,۸۵۰,۰۰۰ |



| مدل | مشخصات | | قیمت مصرف کننده (ریال) |
|----------|---|---|------------------------|
| UCM 6204 |  | UCM6204 IP PBX System, support up to 500 users and 30/45 concurrent calls | ۲۱,۲۰۰,۰۰۰ |
| UCM 6208 |  | UCM6208 IP PBX System, supports up to 800 users and 100 concurrent calls | ۳۴,۶۰۰,۰۰۰ |
| UCM 6102 |  | IP PBX Appliance 2 PSTN trunk FXO ports , 2 analog telephone FXS ports, and up to 50 SIP trunk Gigabit network port with integrated PoE, USB, SD | ۱۷,۱۰۰,۰۰۰ |
| UCM 6104 |  | IP PBX Appliance 4 PSTN trunk FXO ports , 2 analog telephone FXS ports, and up to 50 SIP trunk ,Gigabit network port with integrated PoE, USB, SD | ۲۰,۳۰۰,۰۰۰ |
| UCM 6108 |  | IP PBX Appliance 8 PSTN trunk FXO ports , 2 analog telephone FXS ports, and up to 50 SIP trunk ,Gigabit network port with integrated PoE, USB, SD | ۳۳,۹۰۰,۰۰۰ |








| مدل | مشخصات | | قیمت مصرف کننده (ریال) |
|-----------------------------|---|---|------------------------|
| UCM 6116 |  | IP PBX Appliance 16 PSTN trunk FXO ports, 2 analog telephone FXS ports, and up to 50 SIP trunk , Gigabit network port with integrated PoE, USB, SD | ۵۴,۵۰۰,۰۰۰ |
| UCM 6510 |  | IP PBX Appliance E1/T1/J1 networks Integrated 2 PSTN trunk FXO ports, 2 analog telephone FXS ports, and unlimited SIP trunk options Gigabit network port(s) with integrated PoE, USB, SD card; integrated NAT router with advanced QoS support | ۶۹,۸۵۰,۰۰۰ |
| IP Telephony Gateway | | | |
| HT286 |  | Handy Tone 286 interfaces legacy analog telephones, fax machines, analog conference telephones and other analog devices to IP based telephony networks. | ۲,۲۰۰,۰۰۰ |
| HT486 |  | Handy Tone 486, Analog Telephone adapter, features 2 FXO ports and 1 FXS port as well as a built-in router and DHCP server | ۲,۸۸۰,۰۰۰ |
| HT488 |  | Handy Tone 488, Analog Adapter features both an FXS and FXO port for internet data, voice and PSTN networks | ۳,۱۲۰,۰۰۰ |
| HT701 |  | Single FXS telephone port(supporting 5 REN) single 10/100M Ethernet port, | ۲,۱۸۰,۰۰۰ |









| مدل | مشخصات | | قیمت مصرف کننده (ریال) |
|-------|---|---|------------------------|
| HT702 |  | 2 FXS port, supporting 3 REN and single 10/100M Ethernet port | ۲,۷۰۰,۰۰۰ |
| HT704 |  | 4 FXS port, supporting 3 REN and single 10/100M Ethernet port | ۵,۲۳۰,۰۰۰ |
| HT502 |  | 2 FXS, 2*100 Mb/s Ethernet port | ۲,۶۵۰,۰۰۰ |
| HT503 |  | 1 FXS, 1 FXO, 2*100 Mb/s Ethernet port | ۳,۱۰۰,۰۰۰ |
| HT802 |  | Handy Tone HT802 Supports 2 SIP profiles through 2 FXS ports and a single 10/100Mbps port | ۳,۰۵۰,۰۰۰ |
| HT812 |  | Handy Tone HT812 Supports 2 SIP profiles through 2 FXS ports and dual Gigabit ports | ۳,۲۲۰,۰۰۰ |



| مدل | مشخصات | | قیمت مصرف کننده (ریال) |
|---------|---|---|------------------------|
| HT814 |  | Handy Tone HT814 Supports 4 SIP profiles through 4 FXS ports and dual Gigabit ports | ۶,۷۸۰,۰۰۰ |
| GXW4004 |  | 4 Ports FXS, 2*100 Mb/s Ethernet port | ۶,۳۰۰,۰۰۰ |
| GXW4008 |  | 8 Ports FXS, 2*100 Mb/s Ethernet port | ۱۰,۳۰۰,۰۰۰ |
| GXW4104 |  | 4 Ports FXO, 2*100 Mb/s Ethernet port | ۱۱,۲۰۰,۰۰۰ |
| GXW4108 |  | 8 Ports FXO, 2*100 Mb/s Ethernet port | ۱۴,۲۰۰,۰۰۰ |
| GXW4216 |  | 16 Ports FXS, 2*100 Mb/s Ethernet port | ۲۳,۹۸۰,۰۰۰ |



| مدل | مشخصات | | قیمت مصرف کننده (ریال) |
|----------------------------|---|---|------------------------|
| GXW4224 |  | 24 Ports FXS, 2*100 Mb/s Ethernet port | ۳۱,۰۰۰,۰۰۰ |
| GXW4232 |  | 32 Ports FXS, 2*100 Mb/s Ethernet port | ۴۲,۵۰۰,۰۰۰ |
| GXW4248 |  | 48 Ports FXS, 2*100 Mb/s Ethernet port | ۵۳,۵۰۰,۰۰۰ |
| IP Video Conference | | | |
| GVC 3200 |  | being interoperable with any 3rd party SIP video conferencing platform - thus offering a great option to expand or implement a 3rd party platform. Additionally, since it is based on Android 4.4, the GVC3200 offers full access to all video conferencing apps in the Google Play Store — such as Skype®, Skype for Business®, Google Hangouts™ and more. The GVC3200 sports an innovative, patent-pending embedded MCU that supports up to 9-way conferencing with local mixing between SIP and other protocols. | ۱۷۱,۲۲۰,۰۰۰ |
| GAC 2500 |  | 6 lines, 6 SIP accounts, 7-way voice conferencing Runs Android 4.4 and offers full access to the Google Play | ۲۶,۴۰۰,۰۰۰ |
| WiFi Access Point | | | |
| GWN 7610 |  | GWN7610 offers an impressive Wi-Fi range of 175 meters (575 feet), offers up to 16 different Wi-Fi or VPN networks per device, support for over 250+ clients per GWN7610 and ability to be paired with 3rd-party routers and existing Wi-Fi networks | ۸,۳۸۰,۰۰۰ |